





## A30 TECHNICAL FEATURES

# Auto Level with the highest performances for easy measurements in any construction and survey applications.

Stonex brings the benefits of Auto Level to construction applications at an affordable price with the reliable, easy-to-use A30 Auto Level. The Stonex A30 Auto Level minimizes human error and maximizes the ease of levelling work, allowing increased productivity and performance. In few seconds height difference and distance can be measured. A30 guarantees high accuracy with ±1.5mm standard deviation of 1km round-trip leveling measurement.

The compensator of the Stonex A30 has minimal thermal expansion coefficient, providing unmatched durability and accuracy. Error reducing functions, such as the tilt sensor prevent the system from measuring if the user operates outside the compensator range. Multiple reading for horizontal angles available (1° or 1gon). Any angle can be read thanks to the free rotation characteristics. The Stonex A30 Auto Level is the perfect instrument for your daily levelling tasks.

ACCURACY		AUTOMATIC COMPENSATOR
Standard deviation of 1 km round-trip	±1.5mm	Working range
leveling measurement		Accuracy
		Circular bubble sensitively
DISPLAY RESOLUTION (mm/ft)		
Height	1/0.01	PHYSICAL SPECIFICATIONS
Distance	10/0.1	Dimensions (LxWxH)
		Weight
TELESCOPE		Case weight
Image	Erect	Operating Temperature
Magnification	28x	
Length of tube	215mm	Waterproof/Dustproof
Objective aperture	36mm	
Field of view	1° 25'	
Resolution (JIS standard)	3.5"	
Minimum focus (from the instrument center)	0.3mm	
Horizontal circle diameter	103 mm	
Horizontal circle	1°	
Stadia ratio	100	

### Illustrations, descriptions and technical specifications are not binding and may change



15′ 0.5"/1' ≤8'/2mm

IP66

215x130x135mm 1,76 kg

-20°C to +50° C (-4°F to +122°F)

1,38 kg, accessories included

## STONEX® Part of UniStrong

Via Cimabue 39 - 20851 Lissone (MB) Italy Phone +39 039 2783008 | Fax +39 039 2789576 www.stonex.it | info@stonex.it

STONEX AUTHORIZED DEALER